

OWATROL

® REGISTERED TRADEMARK

SEASONITE

<u>Product:</u>	SEASONITE
<u>Definition</u>	Seasonite is a protective agent for fresh timber exposed to the exterior climate, based on acrylic resins.
<u>Properties</u>	<p>Stabilizes and protects the wood during the first year of weather exposure.</p> <p>Penetrates the surface of the fresh timber, protecting it against excess humidity while leaving the pores free to open naturally.</p> <p>Reduces the risk of crazing, bursting or deformation of the wood under heavy exposures to sunlight or rain.</p> <p>Colorless, straightforward application.</p> <p>Limits the extent of dulling.</p> <p>Allows to obtain, after one year's weather exposure, a sound surface ready for being painted, stained or otherwise protected.</p> <p>Self-protected against mold growth.</p>
<u>Destination</u>	<p>For exterior use only.</p> <p>On new wood only.</p> <p>Ideal for all soft wood, in particular pressure-treated wood.</p> <p>Applicable on terraces, facades, duckboards, or garden furniture, whether of pinewood, Red Cedar or other soft wood.</p> <p>To be utilized directly before or after positioning the touch-dry wood, in a single layer.</p> <p>Not for use on wood already having been exposed to the weather.</p>
<u>Characteristics</u>	<ul style="list-style-type: none">• Presentation Protection for new wood.• Color..... Colorless.• Binder..... Acrylic resins.• Solvent Water• Viscosity at 23 °C ... 20" 8/10th (ISO cup no. 3).• pH Around 7. Contains neither acid nor base.• Density at 18 °C..... Around 1.01 kg/l ± 0.05.• Packagings 1 liter, 3 liters and 15 liters.• Storage period 2 years in original airtight container.• Storage conditions.. Protected from frost and elevated temperatures.• Flash point Non-flammable.• Safety Refer to the safety data sheet and the texts on the packaging, conforming to the legislation in force.
<u>Substrate</u>	<p>The surface whose utilization, nature, quality, state, treatment and pre-treatments are in conformity with current standards.</p> <p>Recommendation: Make sure that the substrate is compatible with a water-dispersed protective product.</p>

Processing

Observing the conditions and instructions laid down by the manufacturer.

Do not apply at ambient temperatures below + 5 °C or above + 30 °C.

Application tool

Brush, roller, spray gun or by immersion.

Dilution

Do not dilute.

Cleaning the tools

Water.

Yield

Theoretically per layer: 5-7 m²/liter.

In practice the yield will vary according to the type, surface condition and absorptive properties of the support, as well as the mode of application.

Drying at 20 °C

Dustfree Around 4-6 hours.

Touch-dry Around 12 hours.

The drying time is influenced by the ambient temperature and the relative air humidity.

Recommendations before application

- Check that the wood is clean, free from spots and touch-dry.
- Homogenize before applying.

Application

- Apply a generous layer of Seasonite on all surfaces of fresh timber to be treated - by brush or roller.
- Pay particular attention to interspaces between planks, and their extremities. To protect shingles, proceed by immersion during 10 minutes, then allow the product to drip off.
- Leave the wood, thus conditioned, during 6-12 months; thereafter clean with Net-trol* if necessary, and then apply a topcoat.

* same manufacturer

This notice supersedes and replaces any previous notice on the same product. Its purpose is to inform our customers on the properties of our product. The information contained in it is based on our knowledge and is the result of tests conducted in a continuous concern for objectivity. The advice presented, in particular as regards maintenance work, is of indicative value only, and cannot come in the place of a specification appropriate to the nature and the state of the actual substrate to be painted. As techniques continually develop, it is up to our customers, before commencing any application, to check with our service staff whether this notice might have been modified by a more recent edition.

Owatrol International SL
C/Aragón 179, 5ª planta
08011 Barcelona – Spain
www.owatrol.com

Edition no. 1 dated October 1, 2000